

Job Name/Location:

Tag #:

Date: _____ For: File Resubmit
 PO No.: _____ Approval Other _____
 Architect: _____ GC: _____
 Engr: _____ Mech: _____
 Rep: _____
 (Company) _____ (Project Manager) _____

PREMTB10U
LG Programmable Wired Remote Controller



Electrical:

Power Supply	Powered from indoor unit
--------------	--------------------------

Surrounding Conditions:

Operating Temperature	32-104 °F
Storage Temperature	-4-176 °F
Humidity	0-90% (non-condensing)

Unit Data:

Dimensions	4-3/4" W x 4-3/4" H x 5/8" D
Maximum Number of Indoor Units (per controller)	16
Maximum Number of Controllers (per group)	2

Standard Features:

- Backlit LCD Display
- Clock

Basic Functions:

- Room temperature display
- Operation - On/Off
- Mode - Auto/Cool/Dry/Heat/Fan Only
- Ventilation mode (for ventilator unit)
- Occupied cooling and heating temperature setpoint
- Unoccupied cooling and heating setback temperature setpoint
- Fan speed - Auto/Low/Med/High/Power
- Discharge vanes - Auto/Swing/Fixed
- Controller lock function
- Static pressure installer setting
- Function setting for plasma filter, electric heat, humidifier, elevation grille, ventilation kit, and auxiliary heat option
- Error code display during unit or system malfunction
- Auto restart on power failure

Advanced Functions:

- Time of day scheduling, 5 events per day with control of occ/unocc, on/off, mode, setpoints, and fan speed
- Two setpoint autochangeover
- Minimum difference between setpoints (0-10°) adjustable deadband
- Setback button
- Timed override button
- Hold
- Occupied/unoccupied
- Set point range lock
- Guard timer

Optional Accessories (sold separately):

- PZCWRC1 - 33-foot Extension Cable Assembly
- PZCWRG3 - Group Control Cable Kit
- PQWRHQOFDB - Wireless Remote Controller

For continual product development, LG reserves the right to change specifications without notice.

© LG Electronics U.S.A., Inc., Englewood Cliffs, NJ. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp. /www.lg-vrf.com

Connectivity:


LG Communications	1 Channel/RS-485 V-Net
-------------------	------------------------

Communications Cabling Specifications (V-Net):

Type	Field supplied
Size	22-3 AWG, twisted, stranded, unshielded
Length*	Up to 164 ft

AWG - American Wire Gauge

*Communications cable can be extended to a maximum of 164 feet between controller and indoor unit using field-supplied cable or the Wired Remote Group Control Cable Assembly (PZCWRG3) or Wired Remote Extension Cable (PZWCRC1), maximum of 4.



- | | |
|-------------------------------|---------------------------------|
| 1 Operation indication screen | 10 Air flow button |
| 2 Set temperature button | 11 Cooling desired temperature |
| 3 Fan Speed button | 12 Function setting button |
| 4 Set back button | 13 Up, Down, Left, Right button |
| 5 Operation mode selection | 14 On/Off button |
| 6 Wireless remote controller | 15 Heating desired temperature |
| 7 Sub function button | 16 Setting/Cancel button |
| 8 Ventilation button | 17 Exit button |
| 9 Reservation button | |

Notes:

Available Functions/features may differ depending on connected system. Communication cable can be extended to a maximum of 164 feet, between controller and indoor unit, by using field supplied cable or the Wired Remote Group Control Cable Assembly (PZCWRG3) or Wired Remote Extension Cable (PZWCRC1), maximum of 4. Must follow installation instructions in the applicable LG installation manual.